

Fusion Four | 3 m

OEHLBACH Fusion Four - Bi-Wiring speaker cable with silver-plated OFC copper, assembled with spade connectors. Precise signal separation for audiophile Hi-Fi.

Product number D1C14222

Weight 2.542kg

Length 260mm

Width 260mm

Height 80mm



Product description

Pre-assembled with Oehlbach Fusion cable lug connectors, this top-class bi-wiring speaker cable continues to set standards in terms of high-fidelity sound characteristics.

It has been specially tuned for hi-fi purists and, in addition to a sophisticated technical concept, also offers a particularly unique product design.

The material of the inner conductor consists of the high-purity and absolutely oxygen-free HPOCC copper. This unique manufacturing process achieves almost monocrystalline transitions within the copper.

The cable construction is based on the consistent separation of the signal paths for the high and low frequency range and achieves a unique transmission quality.

Thus, 12 individually insulated copper strands were additionally wrapped with a wafer-thin copper foil. This unique concept in cable construction requires tremendous manufacturing precision with the main goal of achieving a delay correction between the high and low frequencies.

The low frequencies prefer the more solid inner conductor, while high frequencies tend to travel on the surface and have a higher velocity. The combination of inner conductor and foil results in an unprecedented natural and dynamic sound image.

Product properties

cable cross section	4 x 4,0 mm ²
Features	24kt gold plated contacts, Rigorous separation of signal routes, Made in Germany, 30 years warranty**, Stereo speaker cable
Colour	Black
Quality level	State of the Art
Plug type 1	2 x cable lug
Surface condition	24 carat gold-plated contacts
Connection type	Audio
cable length	3 m
Connector material	solid metal plug
Plug type 2	4 x cable lug
Signal direction	OUT
Product Category	Loudspeaker cable
Inner conductor material	HPOCC® – mono-crystalline oxygen-free copper inner conductor
cable material	fabric sheath
cable geometry	Round
Amplifier power	For amplifier performances of up to 400 watts

More images

