



Primus AB | Black/Gold | 5 m

OEHLBACH Primus AB - Premium USB cable for reliable data transfer and charging. Gold-plated contacts - for PC, printer and peripherals.

| | |
|-----------------------|---------|
| Product number | D1C9544 |
| Weight | 0.332kg |
| Length | 225mm |
| Width | 140mm |
| Height | 40mm |



Product description

The Oehlbach Primus AB USB 2.0 data cable has been specially developed for applications where the highest demands are placed on audio quality. It provides a first-class connection for devices with USB type B ports, such as high-end audio amplifiers, DACs (digital-to-analog converters) and other high-quality audio components. In audiophile setups where lossless and stable data transmission is crucial for perfect sound reproduction, the Primus AB sets the standard.

The reversible USB-A plug enables easy handling, while the monocrystalline, oxygen-free HPOCC copper inner conductor ensures exceptionally pure and precise signal transmission. Thanks to the triple shielding, the signal remains free from electromagnetic interference, which is essential when transmitting high-resolution audio data.

The full metal plugs coated with 24-carat gold ensure optimum contact reliability so that even the smallest nuances in the audio signal are transmitted without loss. The robust fabric jacket protects the cable from mechanical influences and ensures a long service life - ideal for long-term use in demanding audio setups.

The Oehlbach Primus AB is the perfect choice for anyone who doesn't want to compromise on their audio playback and relies on a state-of-the-art connection for transmitting music in studio quality.



Product properties

| | |
|---------------------------------|---|
| Product Category | USB cable, Data cable |
| cable material | Solid plastic casing |
| Features | Perfect for audio transmissions, DACs, external headphone amplifiers, etc., HPOCC® copper conductor for pure, loss-free signal transmission, Triple shielding against interference for perfect audio quality, 24kt gold plated contacts, Audio streaming, 30 years warranty** |
| Plug type 2 | USB-B |
| Shielding | triple shielding |
| Lizenzen | Hi-Speed USB |
| Quality level | State of the Art |
| Shielding construction | 2 x aluminium foil + 1 x copper braiding |
| Connection type | Audio, Data |
| cable length | 5 m |
| Connector material | solid metal plug |
| Signal direction | IN/OUT |
| Inner conductor material | HPOCC® – mono-crystalline oxygen-free copper inner conductor |
| Plug type 1 | USB 2.0 Type A |
| cable geometry | Round |
| Colour | Black/Gold |
| Transmission rate | 480 Mbps |



More images

