



## Fusion Two | 3.50 m

OEHLBACH Fusion Two - Pre-assembled speaker cable set with 24-carat gold-plated spade connectors. Ideal for audiophile Hi-Fi systems.

<b>Product number</b>	D1C110604
<b>Length</b>	260mm
<b>Width</b>	260mm
<b>Height</b>	80mm



### Product description

This extra-class loudspeaker cable preassembled with "Fusion" lugs continues to set standards for high-fidelity sound. This cable has been specially designed with hi-fi purists in mind and it offers a sophisticated technical concept in addition to a particularly discrete product design. The material used for the inner conductor consists of high-purity, oxygen-free HPOCC copper. Monocrystalline-like transitions are achieved within the copper thanks to the unique HPOCC manufacturing process applied. The cable has been structured to rigorously separate the treble and bass transmission routes and thus achieves a unique quality of transmission. Each of the twelve individually insulated copper wires has been wrapped in wafer-thin copper foil. This unique concept in cable construction requires a tremendous degree of precision in the manufacturing process with the main aim of achieving a time delay correction between the high and low frequencies. The low frequencies prefer the more solid inner conductor while the high frequencies tend to move along the surface at greater speeds. The combination of the inner conductor and foil results in an unprecedented natural and dynamic sound.

### Product properties

<b>Features</b>	24kt gold plated contacts, Rigorous separation of signal routes, Made in Germany, 30 years warranty**, Stereo speaker cable
<b>Colour</b>	Black
<b>Plug type 2</b>	2 x cable lug
<b>Quality level</b>	State of the Art
<b>Plug type 1</b>	2 x cable lug
<b>Surface condition</b>	24 carat gold-plated contacts
<b>Connection type</b>	Audio
<b>Shielding</b>	Quadruple shielding
<b>Connector material</b>	solid metal plug
<b>cable cross section</b>	2 x 4.0 mm <sup>2</sup>
<b>Signal direction</b>	OUT
<b>Product Category</b>	Loudspeaker cable
<b>Inner conductor material</b>	HPOCC® – mono-crystalline oxygen-free copper inner conductor
<b>cable material</b>	fabric sheath
<b>cable geometry</b>	Round
<b>Amplifier power</b>	For amplifier performances of up to 400 watts
<b>cable length</b>	3.50 m
<b>Shielding construction</b>	2 x aluminium foil + 2 x copper braiding



More images

