Silverline SP-25 | 6 m

Product number D1C336 Weight 0.5kg



Product description

Excellently processed stereo speaker cable wound on a mini reel. The speaker cable is suitable for amplifier power of up to approx. 250 watts per amplifier channel. The use of silver-plated, oxygen-free OFC copper as conductor material ensures that this speaker cable has an extremely clear and natural sound. The silver plating further improves the reproduction of high frequencies. The cable is also constructed from a large number of ultra-thin stranded copper strands - approx. 0.125 mm cross-section per individual strand. Due to this elaborate processing, a particularly high conductivity and flexibility of the entire cable is achieved.

Product properties

| Plug type 1 | open end |
|--------------------------|--|
| Plug type 2 | open end |
| Flug type 2 | open end |
| Amplifier power | For amplifier performances of up to 250 watts |
| cable material | plastic |
| cable length | 6 m |
| Colour | Transparent silver |
| Inner conductor material | SPC/OFC - silver-plated oxygen-free copper |
| Connection type | Audio |
| Quality level | Excellence |
| Features | Silver content of 8g / kg, 30 years warranty**, Stereo speaker cable, Certified production in Europe |
| Product Category | Loudspeaker cable |
| Signal direction | IN/OUT |
| cable geometry | Round |
| cable cross section | 2 x 2.5 mm ² |

More images







