



Fusion Two B | 3 m

OEHLBACH Fusion Two B - Banana plug, 24-carat gold-plated. Easy installation, secure connection for Hi-Fi loudspeakers, AV receivers and amplifiers.

Product number D1C110613

Weight 1.7kg

Length 260mm

Width 260mm

Height 80mm



Product description

This extra-class loudspeaker cable preassembled with "Fusion" banana plugs continues to set standards for high-fidelity sound. This cable has been specially designed with hi-fi purists in mind and it offers a sophisticated technical concept in addition to a particularly discrete product design. The material used for the inner conductor consists of high-purity, oxygen-free HPOCC copper. Monocrystalline-like transitions are achieved within the copper thanks to the unique HPOCC manufacturing process applied. The cable has been structured to rigorously separate the treble and bass transmission routes and thus achieves a unique quality of transmission. Each of the twelve individually insulated copper wires has been wrapped in wafer-thin copper foil. This unique concept in cable construction requires a tremendous degree of precision in the manufacturing process with the main aim of achieving a time delay correction between the high and low frequencies. The low frequencies prefer the more solid inner conductor while the high frequencies tend to move along the surface at greater speeds. The combination of the inner conductor and foil results in an unprecedented natural and dynamic sound.



Product properties

Features	24kt gold plated contacts, Rigorous separation of signal routes, Made in Germany, 30 years warranty**, Stereo speaker cable
Colour	Black
Quality level	State of the Art
Surface condition	24 carat gold-plated contacts
Plug type 1	2 x banana plug
Connection type	Audio
Shielding	Quadruple shielding
Plug type 2	2 x banana plug
cable length	3 m
Connector material	solid metal plug
cable cross section	2 x 4.0 mm ²
Signal direction	OUT
Product Category	Loudspeaker cable
Inner conductor material	HPOCC® – mono-crystalline oxygen-free copper inner conductor
cable material	fabric sheath
cable geometry	Round
Amplifier power	For amplifier performances of up to 400 watts
Shielding construction	2 x aluminium foil + 2 x copper braiding



More images

