SILVER PLATED SPEAKER CABLE

Silverline SP-25 | 10 m

2.5 mm²

€99.00 RRP incl. VAT

Product number	**D1C185**
EAN	**4003635001851**



250 W · SPOFC SILVER PLATED COPPER · 30 YEAR GUARANTEE · MADE IN EUROPE

HIGHLIGHTS

- Silver content of 8g / kg
- 30 years warranty**
- Stereo speaker cable
- Certified production in Europe

DESCRIPTION

Excellently processed stereo speaker cable wound on a mini reel. The speaker cable is suitable for amplifier power of up to approx. 250 watts per amplifier channel. The use of silver-plated, oxygen-free OFC copper as conductor material ensures that this speaker cable has an extremely clear and natural sound. The silver plating further improves the reproduction of high frequencies. The cable is also constructed from a large number of ultra-thin stranded copper strands - approx. 0.125 mm cross-section per individual strand. Due to this elaborate processing, a particularly high conductivity and flexibility of the entire cable is achieved.

Oehlbach Kabel GmbH
Lise-Meitner-Str. 9, 50259 Pulheim, Germany
Tel. +49 2234 9374 370
info@oehlbach.de · oehlbach.com

TECHNICAL DATA

Weight	0.739 kg
Length	90 mm
Width	90 mm
Height	70 mm
Plug type 1	open end
Plug type 2	open end
cable length	10 m
Amplifier power	For amplifier performances of up to 250 watts
cable material	plastic
Colour	Transparent silver
Inner conductor material	SPC/OFC - silver-plated oxygen-free copper
Connection type	Audio
Quality level	Excellence
Product Category	Loudspeaker cable
Signal direction	IN/OUT
cable geometry	Round
cable cross section	2 x 2.5 mm²

OTHER VARIANTS

VARIANT	PRODUCT NUMBER	EAN	RRP INCL. VAT
Length: 20 m	D1C186	4003635001868	€198.00
Length: 30 m	D1C187	4003635001875	€296.00
Length: 4 m	D1C335	4003635003350	€54.99
Length: 6 m	D1C336	4003635003367	€79.00
Length: 8 m	D1C337	4003635003374	€89.00

Oehlbach Kabel GmbH
Lise-Meitner-Str. 9, 50259 Pulheim, Germany
Tel. +49 2234 9374 370
info@oehlbach.de · oehlbach.com

GALLERY


SILVERLINE 25 SPC


180 W
ULTRA THIN STRANDS
FLEXIBLE
SPOFC
MADE IN EUROPE
SILVERLINE 25 SPC

